

LPS[®] EVR

CLEAN AIR SOLVENT DEGREASER



FEATURES

- High solvent strength
- Fast evaporating
- Low VOC content
- Complies with SCAQMD (South Coast Air Quality Management District) Rule 102
- Complies with CARB/OTC (California Air Resources Board/Ozone Transport Commission) Rules
- Not a Hazardous Air Pollutant (HAP)
- Instant cleaning action
- Excellent replacement for Methyl Ethyl Ketone (MEK)
- Ideal for cleaning metals
- No residue
- No ozone depleting compounds
- Inverta Spray Valve can to be sprayed at almost any angle

PROPERTIES

Appearance:

Clear, colorless liquid.

Odor:

Fragrant, slight orange

Solubility:

Miscible in water.

Specific Gravity:

0.78 - 0.80 @ 68°F (20°C)

VOC Content:

15 g/L (1.7%)

Vapor Density (Air=1):

2.0

KB Value:

>120

Vapor Pressure (mm Hg):

400 @ 104°F (39.5°C)

Vapor Density (Air=1):

2.0

Autoignition Temperature:

869°F (465°C)

HMIS:

1,3,0

Propellant:

Carbon Dioxide

Flashpoint:

CLOSED CUP: -4°F (-20°C)
(Tagliabue)

APPLICATIONS

- Bearings
- Brakes
- Controls
- Chains
- Cables
- Gauges
- Gears
- Hand & Power Tools
- Heavy Equipment
- De-energized Cable Connections
- Instruments



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST
OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

PACKAGES

Net Fill	Part No.
14 oz. (397 g.)	05220
1 gal. (3.78 l.)	05201
5 gal. (18.93 liters)	05205
55 gal. (208 liters)	05255

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2228 • Rev. 5/2012