

LPS[®] TAPMATIC[®] AQUACUT[®]

CUTTING FLUID



FEATURES

- Water-based formula
- Excellent in applications where cooling of the tool is desired
- Non-flammable
- Non-hazardous
- Does not contain sulfur, chlorine or oils
- Safe on all metals, except magnesium
- Corrosion inhibitors prevent flash rusting
- Provides fine finishes
- Cinnamon scent

APPLICATIONS

- Boring
- Broaching
- Drawing
- Drilling
- Engraving
- Facing
- Finishing
- Grinding
- Milling
- Reaming
- Sawing
- Stamping
- Tapping
- Threading
- Turning

PROPERTIES

Color:
Clear Turquoise

Odor:
Cinnamon

Boiling Point:
212°F (100°C)

pH:
8.0 – 9.0

Partition Coefficient (octanol/water):
>1

Specific Gravity (Water=1):
1.0

Vapor Density (Air=1):
~ 0.6

PACKAGES

Net Content	Part No.
16 fl. oz. (0.473 liters)	01216
1 gal. (3.78 liters)	01228
5 gal. (18.93 liters)	01205
55 gal. (208 liters)	01255



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2079 • Rev. 5/2010