



# TAPMATIC® EDGE® CREME

## CUTTING LUBRICANT



### FEATURES

- Biodegradable paste
- Recognized by the USDA BioPreferred™ program
- Excellent for vertical applications
- Can be applied to tools before tapping or reaming
- Squeeze tube allows easy application
- Can be used for tapping, forming, bending, pre-coating fasteners and lubricating rubber seals
- Water rinsable
- Safe on all metals
- Low toxicity

### PACKAGE

Net Content  
10 fl.oz. (0.296 l)

Part No.  
43100



### APPLICATIONS

- Boring
- Broaching
- Drawing
- Drilling
- Engraving
- Facing
- Grinding
- Milling
- Reaming
- Sawing
- Stamping
- Tapping
- Threading
- Turning

### PROPERTIES

Color:

White, Opaque

Flash Point (TCC):

338°F (170°C)

Evaporation Rate (Water=1):

1

Partition Coefficient (octanol/water):

<1

Specific Gravity (Water=1):

0.91-0.93 @ 20 °C

Volatiles:

15%

V.O.C. content:

0 g/L per CARB/OTC

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

**LPS Laboratories** • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

**Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)**

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2141 • Rev. 3/2010